



## Standard CHROMAFLEX® Columns

- Columns are supplied complete with glass barrel, 2 end fittings with 20 µm porosity HDPE bed supports, and screw caps
- Each column is also supplied with 5 feet (1.5 m) of FEP PTFE tubing (1/16" OD with 1.0 cm; 1/8" OD with 2.5 and 4.8 cm), 2 flangeless tubing nuts and 2 flangeless ferrules
- Manufactured from 33 expansion, low extractable borosilicate glass conforming to USP Type I and ASTM E438, Type I, Class A requirements

Part #	Volume (ml)	ID (cm)	Length (cm)	Pressure (psi)	Temp' range (°C)	Tubing Connections (Flangeless fitting)
420830-1500	12	1.0	15	100	0 to 50	1/4"-28
420830-3000	24	1.0	30	100	0 to 50	1/4"-28
420830-6000	47	1.0	60	100	0 to 50	1/4"-28
420830-1000	79	1	100	100	0 to 50	1/4"-28
420830-1200	95	1.0	120	100	0 to 50	1/4"-28
420830-1510	74	2.5	15	75	0 to 50	1/4"-28
420830-3010	147	2.5	30	75	0 to 50	1/4"-28
420830-6010	295	2.5	60	75	0 to 50	1/4"-28
420830-1010	491	2.5	100	75	0 to 50	1/4"-28
420830-1210	589	2.5	120	75	0 to 50	1/4"-28
420830-1520	271	4.8	15	50	0 to 50	1/4"-28
420830-3020	543	4.8	30	50	0 to 50	1/4"-28
420830-6020	1086	4.8	60	50	0 to 50	1/4"-28
420830-1020	1810	4.8	100	50	0 to 50	1/4"-28
420830-1220	2172	4.8	120	50	0 to 50	1/4"-28

